



T (450) 978-3403

1 (888) 528-8518

F (450) 978-2542

4656 Louis B. Mayer, Laval, QC H7P 6E4

www.durodesign.com

LEED® NC 2.2 Certification with DuroDesign Bamboo Flooring

DuroDesign bamboo products contribute to certification under the U.S. Green Building Council's LEED® (Leadership in Energy and Environmental Design) for New Construction 2.2 rating system:

■ MR Credit 6: Rapidly Renewable Materials.

Bamboo is a rapidly renewable resource harvested every six years. The bamboo plant is harvested sustainably and quickly regenerates new growth from its vigorous rhizome system.

■ EQ Credit 4.1: Low-Emitting Materials: Adhesives and Sealants.

The installation adhesive we supply for the optional glue-down installation method of our bamboo flooring has only 86 g/L V.O.C. (<100g/L)

■ EQ Credit 4.2: Low-Emitting Materials: Paints and Coatings.

Should the bamboo floor be finished on-site, our Mp765 Polyurethane clear wood finish has only 200 g/L V.O.C.- well under the 275 g/L limit.

■ EQ Credit 4.4: Low-Emitting Materials: Composite Wood & Agrifiber Products

Adhesives used in our solid and engineered wide-plank bamboo flooring contain no urea formaldehyde.

Contact DuroDesign for more information on how we can help you achieve LEED certification for your next project.

This information sheet was last updated in September 2008.
The most recent revision of this document is always available at <http://www.durodesign.com/>