



T (450) 978-3403

1 (888) 528-8518

F (450) 978-2542

4656 Louis B. Mayer, Laval, QC H7P 6E4

www.durodesign.com

LEED® NC 2.2 Certification with DuroDesign FSC Oak Flooring

DuroDesign FSC oak flooring contributes to certification under the U.S. Green Building Council's LEED® (Leadership in Energy and Environmental Design) for New Construction 2.2 rating system:

■ EQ Credit 4.1: Low-Emitting Materials: Adhesives and Sealants.

The installation adhesive we supply for the optional glue-down installation method of our oak flooring has only 86 g/L V.O.C. (<100g/L)

■ EQ Credit 4.2: Low-Emitting Materials: Paints and Coatings.

Should the oak floor be finished on-site, our Mp765 Polyurethane clear wood finish has only 200 g/L V.O.C.- well under the 275 g/L limit.

■ EQ Credit 4.4: Low-Emitting Materials: Composite Wood & Agrifiber Products

Adhesives used in the plywood substrate of our wide-plank oak flooring contain no urea formaldehyde

■ MR Credit 5.1 and 5.2: Regional Materials.

Our solid-strip FSC Oak flooring is 100% extracted and manufactured in Southern Quebec, Canada and may qualify projects in Eastern Canada and Northeastern USA for this credit.

■ MR Credit 7: Certified Wood.

Durodesign uses FSC-certified oak to encourage and promote environmentally responsible forestry practices.

Contact DuroDesign for more information on how we can help you achieve LEED certification for your next project.

This information sheet was last updated in September 2008.
The most recent revision of this document is always available at <http://www.durodesign.com/>